

Requirements Checklist for PSIP data (U.S.A)
Revision C, January 2010

- ☐ System Time set within +/- one second. [STT]
 - o STT: system_time
 - o STT: GPS_UTC_offset
 - o STT: daylight_savings
- ☐ Must have at least one Major Channel Number same as NTSC Channel number. [TVCT: major_channel_number]. Multiple major channel numbers may be used. (See A/65's Annex B for exceptions and additional usage of major channel number: www.atsc.org)
- ☐ TSID for your DTV station and channels correct (three places).
 - o PAT: transport_stream_id
 - o xVCT: transport_stream_id
 - o xVCT: channel_TSID
- ☐ TSID for other stations correct < if other stations pointed to >. [xVCT: channel_TSID]
TSID List @ <http://www.mstv.org/docs/TSID.pdf> - Not always current, but TSIDs do not change.
- ☐ Four EITs present and correct (at least)
 - o The tables_defined field in the MGT must be 3 + highest numbered EIT.
 - o The table_type fields must have the entries: 0x100 through 0x103 (at least)
 - o EIT0,1, 2, 3: for each VC in the xVCT source_id = source_id in xVCT
 - o For an event, if captioning present, caption_service_descriptor() present
 - o For an event, if content advisory exists, content_advisory_descriptor() present
 - o For an event, if audio present, AC-3_audio_stream_descriptor() present – one per each audio
 - o Optional Audio Language announcement for future programs can be done here
 - o For each event, the actual program title - like the one published in the paper
- ☐ Channel information complete and accurate [TVCT and optionally CVCT]
 - o xVCT: short_name has seven user selected characters identifying each channel
 - o xVCT: program_number matches program_number in PMT (and all the PMTs must be signaled in the PAT)
 - o xVCT: service_location_descriptor() entries match entries in PMT
 - o xVCT: service_type equals 0x02 for MPEG-2 video with or without AC-3 audio

PSIP Options/Other

- ☐ Audio signaling: Must have an AC-3_audio_stream_descriptor() for each audio in the PMT. If multiple audios, must place a component_name_descriptor() for each if they are the same language (to tell them apart). Should place the language code in each AC-3_audio_stream_descriptor(). Strongly recommend place ISO_language_descriptor() in each PMT (was required).
- ☐ Should place the language code in the AC-3_audio_stream_descriptor() in the EIT events.
- ☐ Cable VCT (CVCT) can provide information for cable carriage. For example, send the most used channel number used in your cable carriage in the CVTC fields major_channel_number and minor_channel_number. (It can be the three digit number or a two part number.)
- ☐ Optional Unique identification number for a program: content_identifier_descriptor() in EIT/PMT (A/57B)
- ☐ Optional Long names for Channel: [xVCT: extended_channel_name_descriptor()]
- ☐ Optional text information about a program: [ETT]